

COSASCO® DOUBLE BLOCK AND BLEED SERVICE VALVE

COSASCO® DOUBLE ISOLATION SERVICE VALVE PROVIDES AN EXTRA LAYER OF ISOLATION FROM PROCESS FLUIDS

With a 20% reduction in weight compared to RCS's standard 6000 PSI single isolation service valve, the new COSASCO Double Isolation Service Valve offers maximum safety and easier operation at high pressures. It is compatible with all COSASCO Access Fittings and Magnetic/RBS/RBSA/RSL Retrievers. Attached to the access fitting body, the primary valve is the control which allows the pressurized product to enter the retriever during insertion and removal of COSASCO Solid or Hollow Plug Assemblies. It also contains the pressurized product when the retriever is disconnected. The secondary valve acts as a backup in the unlikely case the primary valve leaks or fails.



COSASCO® Double Block and Bleed Service Valve shown top of the line with Magnetic Retriever attached

Features and Benefits:

- Double Isolation
- Light Weight — 56 lbs (25.4 kg)
- Rated for Pressures up to 6000 PSI
- Rotating Base for Easier Positioning
- Heavy Duty Construction
- Compatible with COSASCO Access Fitting and Magnetic/RBS/RBSA/RSL Retrievers



ROHRBACK COSASCO SYSTEMS
Corrosion Management Solutions
sales@cosasco.com · www.cosasco.com



ISO 9001:2008
Certificate No. FM 10694